



BHS1.com

***Battery Carts & Carriages
Roller Transfer Cart,
Hardwood Transfer Cart,
Traveling Battery Transporter***



BHS Battery Carts offer versatile, dependable alternatives for battery transport demands. Battery Carts are built with operator safety and convenience in mind and can be custom built to unique specifications.

Battery Carts & Carriages

Roller Transfer Cart

The BHS Roller Transfer Cart (RTC) is available in three models with widths from 18" to 40" (457 mm to 1016 mm). For added safety and convenience, roller transfer carts are rated at 3,000 lb (1360 kg) capacity and come standard with floor locks. Note: Roller height required when ordering.

Features & Benefits

- Floor locks for added convenience
- 6" (152 mm) phenolic casters for low rolling resistance
- Spark-proof rollers provide extra levels of safety
- Heavy duty construction means long, dependable life
- All models meet OSHA standards
- Custom designs available to meet your specifications
- 5" to 13" (127 mm to 330 mm) roller heights available
Note: Units with roller heights below 10" (254 mm) use outboard mounted casters and roller heights 10" (254 mm) up to 11" (279 mm) use 5" (127 mm) casters
- Rated 3,000 lb (1360 kg) capacity for heavy loads

Available Models

RTC-18

RTC-30

RTC-40

Product Specifications

	RTC-18	RTC-30	RTC-40
Compartment Width	18" / 457 mm	30" / 762 mm	40" / 1016 mm
Compartment Depth	40" / 1016 mm	40" / 1016 mm	40" / 1016 mm
Shipping Weight	200 lb / 91 kg	300 lb / 136 kg	350 lb / 159 kg



RTC

Battery Carts & Carriages

Traveling Battery Transporter

The BHS Traveling Battery Transporter (TBT) has a track mounted design and is available in two models. The TBT is equipped with removable push bars for added convenience and is rated at 2,400 lb (1088 kg) capacity for heavy loads. Notes: Roller height required when ordering. Required track sold separately.

Available Models

TBT-15

TBT-21

Required Accessories

Single Guidance Track - 3" (SGT-C3)

3" (76 mm) C-channel track designed for use with phenolic wheel

Features & Benefits

- Allows for one person changing operations in most applications
- All models meet OSHA safety standards
- Removable push bars for added convenience
- Rated 2,400 lb (1088 kg) capacity for heavy loads
- Spark-proof poly coated rollers make transfers safe and easy
- Track mounted design

Product Specifications

	TBT-15	TBT-21
Compartment Width	15" / 381 mm	21" / 533 mm
Compartment Depth	40" / 1016 mm	40" / 1016 mm
Shipping Weight	150 lb / 68 kg	175 lb / 79 kg



TBT shown with SGT-C3 (sold separately)

Battery Carts & Carriages Hardwood Transfer Cart

The BHS Hardwood Transfer Cart (HTC) utilizes plastic lumber decking and is available in two models. The HTC is rated at 3,000 lb (1360 kg) capacity for heavy loads and 6" (152 mm) phenolic casters are standard on all models.

Available Models

HTC-3040

HTC-4040

Product Specifications

	HTC-3040	HTC-4040
Overall Width	34" / 863 mm	44" / 1117 mm
Compartment Width	30" / 762 mm	40" / 1016 mm
Compartment Depth	40" / 1016 mm	40" / 1016 mm
Shipping Weight	200 lb / 91 kg	230 lb / 104 kg
Deck Height	11" / 279 mm	11" / 279 mm

Features & Benefits

- Plastic interlay lumber deck
- Heavy duty construction for long life and added dependability
- 6" (152 mm) phenolic casters available on all models
- Custom designs available to meet your specifications
- Rated 3,000 lb (1360 kg) capacity for heavy loads



HTC

