



PRESENTING OUR NEWEST INNOVATION **PROPANE TUGGER TRAILER**

The BHS Propane Tugger Trailer (PTT-6) improves ergonomics and productivity for facilities that use LP forklifts. This unit combines a six-tank propane cart with a hydraulic-lift crane to simplify LP tank changes.

Improve Safety During LP Tank Change-Out

Liquid propane tanks store contents under pressure, at dangerously cold temperatures, and can injure bystanders if ruptured; the PTT-6 improves safety during all tank-handling tasks.



Efficient Tank Exchange

The PTT-6 carries six 8-gallon LP tanks, allowing users to refuel multiple lift trucks on a single run. The integrated crane lifts a full tank, swiveling and traveling vertically to place it gently onto the truck's locating pin.



Simple Controls

A hand pump raises the hydraulic crane's lifting beam, while a release lever causes a controlled descent.



ERGONOMIC HANDLING

Four horizontal tank beds give the cart a low profile; the top two swivel open for access to tanks located below. Two vertical tank wells are positioned close to the ground to limit lifting even when handling lighter empty tanks.

PROPANE TUGGER TRAILER

CYLINDER STORAGE & TRANSPORT EQUIPMENT

Ergonomic Crane



250 lb capacity lifting arm rotates 360° to transfer full tanks with ease

Durable Construction

Heavy-duty steel construction with a chemical-, impact-, and scratch-resistant powder-coat finish

Simple Controls

A hand pump powers the hydraulic lifting arm and a release lever controls descent

Ergonomic Handling

Provides ergonomic handling for six 8-gallon LP tanks

Rigid Hitch



Pintle hook trailer hitch offers secure attachment to an additional trailer

Universal Tow Bar

Compatible with all types of electric tuggers



Secure Storage



Pair the PTT-6 with BHS' Cylinder Storage Cage for a complete solution offering secure storage and simple transport of your forklift propane tanks

Mobility

Center steer design utilizes two rigid and four swivel casters for exceptional maneuverability

Rotating Shelving



Locking pins secure two upper cradles that independently swing outwards, providing access to the lower shelf

Model	Overall Length	Overall Width	Overall Height	Capacity	Weight
PTT-6	90.5" / 2299 mm	36" / 914 mm	65" / 1651 mm	3,000 lb / 1361 kg	650 lb / 295 kg